

TECHNICAL SAFETY DATA SHEET

HD 50 MORTAR REMOVER

CERTIFICATION: NONE

Section 1. Product Description and Picture

HD 50 is a heavy duty, multi-functional acid cleaner.

Used effectively as a cement residue cleaner. Also used as a brick cleaner. Effectively degreases and removes heavy soil from paving. Can also be used as a de-ruster and toilet bowl cleaner. Also used as an acid edge prior to epoxy or painting of cement floors

Advantage: Multifunctional, good cleaning ability provides quick results.

HD 50 is a must have product in all industries that demands an easy to use, heavy duty, effective acid based cleaner.





Section 2. Technical Data

Colour : Yellow / Amber
Appearance : Non viscous liquid

Odour : Acid Sweet

pH :

Flash Point : Not Applicable Dissolvable : In water only

Section 3. Properties

Water soluble cleaner, hydrochloric acid, cleaning surfactants, natural cleaning derivatives, and water soluble cleaning solvents.

Section 4. Method of Application

Can be sprayed on, or by scrubbing method. For cleaning paving, pour on to surfaces, leave for 2 – 3 minutes, scrub and rinse immediately.

Dilute with water, dilute to suit cleaning application.

Application	Product	Water Minimum	Water Maximum
Light Duty	1	20	30
Medium Duty	1	10	20
High Duty	1	5	10



Section 5. Health and Safety Precautions

Storage

Cool storage. Avoid sunlight. Keep the container sealed

Skin

Avoid skin contact.

Use gloves.

Should skin come into contact with product – wash skin with water, a barrier cream or moisturising cream should be applied to the affected area.

Eyes

Avoid eye contact.

Use goggles.

Eyes should immediately be washed out with copious volumes of water or eye wash solutions.

Ingestion

Do Not Ingest.

Consult a physician immediately.

Section 6. Spillage and Disposal

Empty containers, or used containers should be sealed and returned to the supplier, or dumped at a waste disposal site according to local regulations. If this is not possible, container should be thoroughly rinsed with soap and water and stored well closed until it can be disposed of.

Technical Assistance

The Technical Sales Representative will provide assistance as required to the customer, before, during and after a trial. Should any problem arise with the application of the product, the Technical Sales Rep should be contacted immediately.

Head Office contact number is: 011-314 0714

The information contained herein is based on our best current technical knowledge of the product concerned and is given in good faith. The attention of end users is drawn to (amongst other things) the element of risk consequent to the use of the product for purposes other than that for which it was intended. In no way does the document remove the need for the user of this product to fully understand and apply statutory requirements. It is the user's sole responsibility to take due precautions relative to the use made of the product. All the information included herein is intended onto to assist the reader in fulfilling his or her statutory duty connected with the use of hazardous materials. This list of information must not be considered as exhaustive and does not exonerate the reader from taking other precautions described in documents other than those mentioned concerning the storage and use of the product for which he or she remains the sole person responsible.