

TECHNICAL SAFETY DATA SHEET

HD84 - BIO TECH CTX 1 (Ready to use)

Section 1. Product Description and Picture

Multi-Purpose bio-formulation surface cleaner and deodoriser - Ready to Use Formula

Bio Tech GTX 1 microbial consortium demonstrates superior enzyme performance for use in multiple applications. It exhibits a broad range of degradation capabilities needed for a multi-purpose product efficacious in maintenance of drain line and grease traps, improving septic and waste degradation and cleaning, and odour control.

In their natural environment, bacteria produce hundreds of enzymes in response to the organics present in their environment. They produce extracellular enzymes that break down proteins, starches, fats, oils, greases, urine, esters and toilet tissue into smaller particles outside the bacterial cell. The bacteria then transport the smaller particles across their cell membrane for use as an energy source and for building of new cellular components. Since bacteria detect the organics present as potential food and produce specific enzymes to breakdown these organics, it is a very efficient system. Many different enzymes are required to completely breakdown a substrate.

The bacillus consortium in Bio Tech GTX 1 produces seven separate enzymes to ensure a swift degradation of key organic contaminants to ensure drain lines, grease traps, septic systems and surfaces are biologically cleaned and odours controlled. Although many bacteria can utilise these organics as food sources, it is the bacteria with the most rapid production of these enzymes that provide the most dramatic effects. Technologically the most advanced formulation on the South African market.

Safety of Bio Tech GTX 1 Consortium:

Bio Tech GTX 1 contains a blend of safe Bacillus microorganisms. Toxicity studies done by an independent laboratory shows that Bio Tech GTX 1 consortium has no acute oral toxicity, no acute dermal toxicity, and no acute inhalation toxicity at maximal test dose. Acute dermal irritation and acute eye irritation studies classify Bio Tech GTX 1 consortium as non-irritating. Bio Tech GTX 1 consortium does not elicit a skin sensitisation reaction.

Section 2. Benefits & Features

Data Sheet			
Benefits	 Drain lines and grease traps – degrades and eliminates organics found in drain lines and grease traps. Regular addition of Odorite™ Ultra Drain Purge maintains a cleaner and odour-free system. Septic and waste treatment – maintains effective activity in septic systems, eliminating the need for excessive pumping. Eliminates odours caused by incomplete digestion of malodorous volatile fatty acids. Bathroom cleaning and odour control – penetrates cracks, crevices and pores of surfaces where organics accumulate, removing the organics leaving a visually cleaner surface. Provides long term odour control by removing the organics that cause odours and prevents their return. 		
Features	 A stable consortium of safe Bacillus spores Production of multiple enzymes providing a wide range of degradation capabilities A synergistic blend that works in concert to provide superior performance across multiple applications Excretion of high levels of amylase, cellulase, lipase, protease, urease, esterase & xylanase enzymes Ability to work under aerobic and anaerobic conditions Single product simplicity for multi-application flexibility 		



Section 3. Characteristics

- Bacteria Counts: 1,02 X 108 /ml (102 million spores/ml)
- Bacteria Type: Bacillus consortium producing the following enzymes:

Protease – breaks down proteins (e.g. meat, excreted/secreted proteins) into amino acids

Lipase – breaks down fats/grease into fatty acids & glycerol. If not broken down, fats can go rancid & lead to off-odours and blocked drains/fat grease traps.

Amylase – starch acts as a glue for dirt – amylases catalyse the break-down of starch into sugars which are then further used as a food source by the bacillus

Cellulase – breaks down cellulosic material

Urease - catalyzes the hydrolysis of urea into break-down products.

Esterase - splits esters into an acid and an alcohol in a chemical reaction with water called hydrolysis. Esters have characteristic odours most of which are pleasant/fruity, however can also include onion/garlic and worse odours

Xylanase – help in breaking down plant cell walls.

o What this means – the bacillus use the multitude of enzymes produced to break down the components of malodour and staining to provide microbial cleaning at the smallest level of dirt/contamination.

Salmonella : Not detectedAppearance : Clear liquid

Fragrance : Pleasantly perfumed

Shelf-life: Two years; maximum loss of 1.0 log at recommended storage condition

Section 4. Dosage Rates

Bio Tech GTX 1 can be further diluted dependent on application to a maximum of 1:9. Must be used on the day - do not store

1. FOOD WASTE – DOMESTIC & INDUSTRIAL: reducing blockage of drains, pipes: treatment of effluent not on main drainage: reduction of odours and general purpose cleaning

Area	Dilution	Initial Dose Rate	Regular Maintenance Rate	Method od Application
Effluent tanks	As is	400g per typical house	100g per month	Through any convenient access
				point e.g. toilet
Cess Pits	As is	400g per typical house	100g per month	Through any convenient access
				point e.g. toilet
Urinals	As is		Spray twice daily	
Bathroom	1:9		Daily cleaning	As per cleaning method
Drains	As is	15g	15g/month	Direct

2. AGRICULTURE WASTE: reduction of high solids/crusting of waste: liquefaction and cleaning (i.e. cowsheds, piggeries, poultry farms etc.)

Area	Dilution	Initial Dose Rate	Regular Maintenance Rate	Method od Application
Buildings		1kg/10 tons animal weight	Weekly for two weeks, 500gm/week	Spray over surfaces
Floors	1:9	1kg/ 120m²	1kg/120m²	Spray over surfaces
Effluent Pits		1kg/250 000 litres	Weekly	Spray over cone
Ponds & Slurry		1kg/250 000 litres	Weekly	Spray over cone
Tanks				



3. SEWAGE PLANTS: general aid to processing.

Area	Dilution	Initial Dose Rate	Regular Maintenance Rate	Method od Application
Trickling filters	1:9	1kg/4,5 million litres	500g/4,5 million litres per week	Add to primary settling tank
Anaerobic digesters		500g/45 000 litres	Repeat for 3 days then per week	Add to inflow pipe
Retention ponds		500g/45 000 litres	Repeat for 3 days then per week	Add to inflow pipe
Activated sludge		500g/45 000 litres	Repeat for 3 days then per week	Add to inflow pipe

Bio Tech GTX 1 Concentrate is designed as a bio-technical aid to treatment of organic waste material offering liquefaction and reduction of solids, reduction of odour, easier disposal of waste, aids general cleaning of soiled areas, safety in operation of effluent systems, offers a viable alternative to current processing techniques using a bio-technical approach.

The information contained in this leaflet is to the best of our knowledge, true & accurate, but any recommendations or suggestions which may be made are without guarantee since the conditions of use are beyond our control. No license or immunity under any patents is granted or implied. Green Worx CS does not guarantee that the above products can be used as described without prior positive testing or the use of these products does not infringe third parties' patent rights.

Section 5. Other Information

The proprietary bacterial strains used in Green Worx CS products are all natural strains and have not been subject to any gene splicing or recombinant technologies (No GMO). They are beneficial and classified as Type 1 (harmless organisms).

Section 6. Directions for Use

Always shake the concentrate before mixing to disperse your probiotic workers!

Dilute FCC in a 1:9 ratio; 1 part FCC to 9 parts water for heavy soiled floors and carpets Dilute

FCC in a 1:99 ratio; 1 part FCC to 99 parts water Clene il DISPOSA BLESS

1 Bushbuck Close - Unit 2, Corporate Park - South, Midrand

sectleh +2711-314-0714 spermailusales@hyg.co.zareasWeb: www.hyg.co.za